



CROSS APTML CASHLESS

Payment terminal

APTML CASHLESS can function as part of the CrossPark parking system or as a universal payment terminal where full control and secure payment is required (bus/train/museum fees etc.).

KEY FEATURES

- 17" LCD touchscreen
- QR code ticket reader
- Payment only by payment cards
- Receipt printer
- Language selection options
- IP intercom
- Possibility to collect additional fees
- Heating / Ventilation

OPTIONAL

- RFID
- IP camera
- IR relay

TECHNICAL SPECIFICATIONS

Power supply	230 / 50 Hz
Power consumption	Power 230 VAC 300 W + 250 W heating
Control voltage	12 V DC / 24 V DC
Ingress protection	IP 44
Dimensions	1624 x 450 x 352 mm
Weight	110 kg
Operation temperature range	-20 up to +50 °C



CROSS APTML

Payment terminal



APTML functions as part of the CrossPark parking system or as a universal payment terminal where full control and secure payment is required (street parking fees, bus/train/museum tickets, etc.).

KEY FEATURES

- 17" LCD touchscreen
- 8" LCD touchscreen
- QR code ticket reader
- Payment by coins, banknotes and payment cards
- Cash back (coins, banknotes)
- Printer for receipts
- Language selection options
- IP intercom
- Possibility to collect additional fees
- Heating / Ventilation

OPTIONAL EQUIPMENT

- Motor parking ticket reader/upper reading
- Four-side bar code parking ticket reader
- RFID card reader
- City cards integration
- Payment by card
- GSM modem for remote monitoring
- IP video intercom
- "P" sign on the pole

TECHNICAL SPECIFICATIONS

Power supply	230 V / 50 Hz
Power consumption	Max. 2 300 W incl. service socket (heating included)
Nominal power	300 W
Ingress protection	IP 44
Dimensions	1624 x 450 x 352 mm
Weight	110 kg
Operating temperature	-20 up to + 50 °C
Color	RAL 7015; RAL 7040